



**SYSTEM COMPONENTS:**

- LOW FREQUENCY DRIVER:** LE15A (2)  
 Cone Kit: C16R2215  
 Nom. Impedance: 16 Ohm  
 Dynamic Test Input V: 10  
 Sweep Frequency Hz: 20-1200  
 D.C. Resistance Ohms: 7.6 min/9.2 max  
 Gap Gauge: .057"  
 Notes:  
 If Not Serviceable, Replace With: 2235H  
 Visual Change: Yes  
 Baffle Modification: No  
 Exact Acoustic Replacement: No. Use as last resort.  
 Replace both units in a stereo pair.  
 Additional Parts Currently Available\*:  
 Dome: 21514  
 Mounting Gasket: 34499  
 Trim Gasket: 21058
- MID RANGE DRIVER:** 375 (2)  
 Diaphragm Kit: D16R2440  
 Nom. Impedance: 16 Ohm  
 Dynamic Test Input V: 3.5  
 Sweep Frequency Hz: 350-1200  
 D.C. Resistance Ohms: 7.3 min/8.6 max  
 Gap Gauge: .036"  
 Notes:  
 D16R2441 can be used as alternate in pairs.  
 If Not Serviceable, Replace With: 2441  
 Visual Change: Yes  
 Baffle Modification: No  
 Exact Acoustic Replacement: No. Slightly different  
 Replace both units in a stereo pair.

- HIGH FREQUENCY DRIVER:** 075 (2)  
 Diaphragm Kit: D8R075  
 Nom. Impedance: 8 Ohm  
 Dynamic Test Input V: 7  
 Sweep Frequency Hz: 1000-3000  
 D.C. Resistance Ohms: 5.7 min/6.7 max  
 Gap Gauge: .025"  
 Notes:  
 Do not crease diaphragm.  
 Test with network.  
 If Not Serviceable, Replace With: Currently Available.  
 Can also be replaced with 2402H.  
 Visual Change: Yes  
 Baffle Modification: No  
 Exact Acoustic Replacement: Yes  
 Additional Parts Currently Available\*:  
 Mounting Gasket: 51795

**SYSTEM SPECIFICATIONS:**

- Nom. Impedance: 8 Ohm  
 Power Capacity: 125 Watts Continuous Program  
 Crossover Frequencies: 500 Hz, 7000 Hz  
 Sensitivity: 82dB (1 Watt @ 15 Feet)  
 Enclosure Dim: 35-1/2" x 103-5/8" x 24-1/16" D  
 90cm x 263cm x 61cm  
 Shipping Weight: 695 lbs. - 316 kg.  
 Additional Parts Currently Available\*:  
 Binding Posts: Red: 10243  
 Black: 10244

\*Other parts may also be available. Check with JBL for details.