



**SYSTEM COMPONENTS:**

<b>LOW FREQUENCY DRIVER:</b>	306G-2
Cone Kit:	C4R306G-2
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	4
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	4.6 min/5.8 max
Gap Gauge:	.051"
Notes:	
If Not Serviceable, Replace With:	306G-3
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different. Replace both units in a stereo pair.
<b>Additional Parts Currently Available*:</b>	
Dome:	60372
<b>HIGH FREQUENCY DRIVER:</b>	010
Diaphragm Kit:	Not Available. Defective driver should be replaced.
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	3

**HIGH FREQUENCY DRIVER (Cont'd)**

Sweep Frequency Hz:	2000-12000
D.C. Resistance Ohms:	2.4 min/2.9 max
Gap Gauge:	N/A
Notes:	
If Not Serviceable, Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A

**SYSTEM SPECIFICATIONS:**

Nom. Impedance:	8 Ohm
Max Recommended Amp	
Power Range:	10-60 Watts Per Channel
Crossover Frequency:	4000 Hz
Sensitivity:	87dB (1 Watt @ 1 Meter)
Enclosure Dim:	14-3/4" x 10" x 9-1/4" D 375mm x 254mm x 235mm
Shipping Weight:	39 lbs. - 17.7 kg./pair
<b>Additional Parts Currently Available*:</b>	
Grill:	G216
Binding Posts:	Red: 63635 Black: 63636

\*Other parts may also be available. Check with JBL for details.