



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	308G-2
Cone Kit:	C4R308G-2
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	4.8 min/5.9 max
Gap Gauge:	.051"
Notes:	
If Not Serviceable, Replace With:	308G-1 or 508G
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different.
	Replace both units in a stereo pair.

Additional Parts Currently Available*:

Dome:	61521
Mounting Gasket:	59707

HIGH FREQUENCY DRIVER:	011
Diaphragm Kit:	Diaphragm Kit not available. Defective driver should be replaced.
Nom. Impedance:	4 Ohm

HIGH FREQUENCY DRIVER (Cont'd)

Dynamic Test Input V:	3
Sweep Frequency Hz:	2000-12000
D.C. Resistance Ohms:	2.7 min/3.3 max
Gap Gauge:	N/A
Notes:	
If Not Serviceable, Replace With:	012
Visual Change:	Yes
Baffle Modification:	Yes
Exact Acoustic Replacement:	No. Slightly different.
	Replace both units in a stereo pair.

SYSTEM SPECIFICATIONS:

Nom. Impedance:	} NOT AVAILABLE
Rec. Amp Power Range:	
Crossover Frequencies:	
Sensitivity:	
Enclosure Dim:	
Shipping Weight:	
Additional Parts Currently Available*:	
Binding Posts: Red:	63635
Black:	63636

*Other parts may also be available. Check with JBL for details.