



**SYSTEM COMPONENTS:**

<b>LOW FREQUENCY DRIVER:</b>	115H
Cone Kit:	C8R115
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	4
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	3.2 minimum 3.6 maximum
Gap Gauge:	.051"
Notes:	Aquaplas On Cone
If Not Serviceable,	
Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A
Additional Parts Currently Available*:	
Dome:	62183
Mounting Gasket:	62571
Trim Gasket:	62184

<b>HIGH FREQUENCY DRIVER:</b>	034
Diaphragm Kit:	D8R034
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	2.5
Sweep Frequency Hz:	200-2000
D.C. Resistance Ohms:	5.4 minimum 6.6 maximum

**HIGH FREQUENCY DRIVER (Cont'd)**

Gap Gauge:	.031"
Notes:	Test With Network
If Not Serviceable,	
Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic	
Replacement:	N/A
Additional Parts Currently Available*:	
Mounting Gasket:	57754
Screen:	60424
Screen Gasket:	60752

**SYSTEM SPECIFICATIONS:**

Nominal Impedance:	8 Ohm
Power Capacity:	100 Watts
Crossover Frequency:	2.5 kHz
Sensitivity:	87dB (1 Watt @ 1 Meter)
Enclosure Dim:	14-3/4" x 9-3/8" x 7-3/16" D 375mm x 238mm x 183mm
Shipping Weight:	35 lbs. - 15.8 kg. (Pair)
Additional Parts Currently Available*:	
Binding Posts: Red:	56131
Black:	56130

\*Other parts may also be available. Check with JBL for details.