



SYSTEM COMPONENTS:

- LOW FREQUENCY DRIVER:** 116A
 Cone Kit: C8R116A
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 5
 Sweep Frequency Hz: 30-1200
 D.C. Resistance Ohms: 5.0 minimum
 5.4 maximum
 Gap Gauge: .044"
 Notes: Dome Inverted
 If Not Serviceable, Replace With: 116H-3
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No.
 Slightly different. Replace both units in a stereo pair.
 Additional Parts Currently Available*:
 Dome: 50201
 Terminal Board: 52348
 Mounting Gasket: 52671
 Trim Gasket: 52316
- HIGH FREQUENCY DRIVER:** LE26
 Diaphragm Kit: D8RLE26
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 3
 Sweep Frequency Hz: 500-1200

- HIGH FREQUENCY DRIVER (Cont'd)**
 D.C. Resistance Ohms: 3.4 minimum
 4.3 maximum
 Gap Gauge: .029"
 Notes: Plastic Flange
 If Not Serviceable, Replace With: 035TiA
 Visual Change: Yes
 Baffle Modification: Yes
 Exact Acoustic Replacement: No. Use as a last resort. Replace both units in a stereo pair.
 Additional Parts Currently Available*:
 Trim Ring: 57732
 Mounting Gasket: 50949-02
 Dome: 21606

SYSTEM SPECIFICATIONS:

- Nominal Impedance: 8 Ohm
 Power Capacity: 35 Watts
 Continuous Program
 Crossover Frequency: 2.5 kHz
 Sensitivity: 87dB (1 Watt @ 1 Meter)
 Enclosure Dim: 21" x 13" x 10" D
 533mm x 330mm x 254mm
 Shipping Weight: 29 lbs. - 13.1 kg.
 Additional Parts Currently Available*:
 Binding Posts: Red: 56131
 Black: 56130

*Other parts may also be available. Check with JBL for details.