



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	127A
Cone Kit:	C8R127A
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	30-1200
D.C. Resistance Ohms:	4.8 minimum 5.6 maximum
Gap Gauge:	.044"
Notes:	
If Not Serviceable,	
Replace With:	125HR
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No.
	Slightly different. Replace both units in a stereo pair.
Additional Parts Currently Available*:	
Dome:	50201
Mounting Gasket:	52089
Trim Gasket:	52315
HIGH FREQUENCY DRIVER:	033
Diaphragm Kit:	D8R033
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	200-1200

HIGH FREQUENCY DRIVER (Cont'd)

D.C. Resistance Ohms:	3.6 minimum 4.4 maximum
Gap Gauge:	.031"
Notes:	Test With Network
If Not Serviceable,	
Replace With:	No replacement
	available. 034 not safe for L40 System.
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A
Additional Parts Currently Available*:	
Mounting Gasket:	57754

SYSTEM SPECIFICATIONS:

Nominal Impedance:	8 Ohm
Max Recommended	
Amp Power:	70 Watts
Crossover Frequency:	1800 Hz
Sensitivity:	88dB (1 Watt @ 1 Meter)
Enclosure Dim:	23" x 15" x 11-7/8" D 584mm x 381mm x 302mm
Shipping Weight:	44 lbs. - 20 kg.
Additional Parts Currently Available*:	
Binding Posts: Red:	56131
Black:	56130
Grille Pegs:	59266

*Other parts may also be available. Check with JBL for details.