



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER: 127H
 Cone Kit: C8R127A
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 5
 Sweep Frequency Hz: 30-1200
 D.C. Resistance Ohms: 4.8 minimum
 5.6 maximum

Gap Gauge: .044"

Notes:
 If Not Serviceable,

Replace With: 125HR

Visual Change: Yes

Baffle Modification: No

Exact Acoustic Replacement: No.

Slightly different. Replace both units
 in a stereo pair.

Additional Parts Currently Available*:

Dome: 50201

Terminal Board: 52348

Mounting Gasket: 52089

Trim Gasket: 52315

HIGH FREQUENCY DRIVER: 033
 Diaphragm Kit: D8R033
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 5
 Sweep Frequency Hz: 200-1200

HIGH FREQUENCY DRIVER (Cont'd)

D.C. Resistance Ohms: 3.6 minimum
 4.4 maximum

Gap Gauge: .031"

Notes: Test With Network

If Not Serviceable,

Replace With: No replacement
 available. 034 not safe for L40A System.

Visual Change: N/A

Baffle Modification: N/A

Exact Acoustic Replacement: N/A

Additional Parts Currently Available*:

Mounting Gasket: 57754

SYSTEM SPECIFICATIONS:

Nominal Impedance: 8 Ohm

Max Recommended

Amp Power: 150 Watts

Crossover Frequency: 1800 Hz

Sensitivity: 88dB (1 Watt @ 1 Meter)

Enclosure Dim: 23" x 15" x 11-7/8" D

584mm x 381mm x 302mm

Shipping Weight: 44 lbs. - 20 kg.

Additional Parts Currently Available*:

Binding Posts: Red: 56131

Black: 56130

*Other parts may also be available. Check with JBL for details.