



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:
 130A
 Cone Kit: C8R2220
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 10
 Sweep Frequency Hz: 20-1200
 D.C. Resistance Ohms: 5.2 minimum
 6.2 maximum

Gap Gauge: .057"

Notes:
 If Not Serviceable,

Replace With: 2220H

Visual Change: Yes

Baffle Modification: No

Exact Acoustic Replacement: No.

Slightly different. Replace both units
 in a stereo pair.

Additional Parts Currently Available*:

Dome: 21042

Trim Gasket: 21058

HIGH FREQUENCY DRIVER:
 LE175
 Diaphragm Kit: D16R2410
 Nom. Impedance: 16 Ohm
 Dynamic Test Input V: 3.5
 Sweep Frequency Hz: 550-1200
 D.C. Resistance Ohms: 5.9 minimum
 7.0 maximum

HIGH FREQUENCY DRIVER (Cont'd)

Gap Gauge: .031"

Notes:

If Not Serviceable,

Replace With: 2425J

Visual Change: Yes

Baffle Modification: No

Exact Acoustic Replacement: No.

Slightly different. Replace both units
 in a stereo pair.

Additional Parts Currently Available*:

Horn: H91

(Lens L91 No
 Longer Available)

SYSTEM SPECIFICATIONS:

Nominal Impedance: 8 Ohm
 Power Capacity: 60 Watts
 Continuous Program
 Crossover Frequency: 1200 Hz
 Sensitivity: 88dB (1 Watt @ 15 Feet)
 Enclosure Dim: 21-3/4" x 29-5/8" x 17-3/4" D
 (Without Base)
 55cm x 75cm x 45cm
 Shipping Weight: 109 lbs. - 45 kg.
 Additional Parts Currently Available*:
 Binding Posts: Red: 10243
 Black: 10244

*Other parts may also be available. Check with JBL for details.