



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:
 Cone Kit: LE10
 Nom. Impedance: C8RLE10A
 Dynamic Test Input V: 8 Ohm
 Sweep Frequency Hz: 6
 D.C. Resistance Ohms: 20-1200
 Gap Gauge: 4.4 minimum
 Notes: 5.0 maximum
 Dome Inverted.

If Not Serviceable,
 Replace With: LE10H-1
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No.
 Slightly different. Replace both units
 in a stereo pair.

Additional Parts Currently Available*:
 Dome: 21514
HIGH FREQUENCY DRIVER:
 Diaphragm Kit: LE20-1
 Nom. Impedance: D8RLE20
 Dynamic Test Input V: 8 Ohm
 6

HIGH FREQUENCY DRIVER (Cont'd)

Sweep Frequency Hz: 1000-6000
 D.C. Resistance Ohms: 3.7 minimum
 4.2 maximum
 Gap Gauge: .029"
 Notes: Test With Network
 If Not Serviceable,
 Replace With: 035TiA
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic
 Replacement: No.
 Use as a last resort. Replace both units
 in a stereo pair.

Additional Parts Currently Available*:
 Trim Ring: 21600

SYSTEM SPECIFICATIONS:

Nominal Impedance: 8 Ohm
 Power Capacity: 30 Watts
 Crossover Frequency: 3000 Hz
 Sensitivity: } **NOT AVAILABLE**
 Enclosure Dim: }
 Shipping Weight: 47-1/2 lbs. - 21.5 kg.
 Additional Parts Currently Available*:

*Other parts may also be available. Check with JBL for details.