



LT-1 SCHEMATIC

SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	LT-1
Cone Kit:	C8RLT-1
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	4
Sweep Frequency Hz:	20-1000
D.C. Resistance Ohms:	5.6 min/6.6 max
Gap Gauge:	.051"
Notes:	One Piece Baffle/ Woofer Frame
If Not Serviceable, Replace With:	No Replacement Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A
Additional Parts Currently Available*:	
Dome:	62872
Trim Gasket:	61920
HIGH FREQUENCY DRIVER:	024
Diaphragm Kit:	D4R024
Nom. Impedance:	4 Ohm
Dynamic Test Input V:	5
Sweep Frequency Hz:	200-1200
D.C. Resistance Ohms:	3.5 min/4.5 max

HIGH FREQUENCY DRIVER (Cont'd)

Gap Gauge:	.036"
Notes:	
If Not Serviceable, Replace With:	Currently Available
Visual Change:	N/A
Baffle Modification:	N/A
Exact Acoustic Replacement:	N/A

SYSTEM SPECIFICATIONS:

Nom. Impedance:	8 Ohm
Power Handling:	50 Watts Continuous/ 100 Watts Peak
Frequency Response:	100 Hz - 20 kHz
Crossover Frequency:	4000 Hz
Sensitivity:	87dB (1 Watt @ 1 Meter)
Enclosure Dim:	9-5/8" x 6-1/4" x 5" D 244mm x 159mm x 127mm
Shipping Weight:	13-1/2 lbs. - 6.1 kg.
Additional Parts Currently Available*:	
Grill:	GRLT-1
Mounting Brackets:	62803-01 (Bracket Knobs No Longer Available)

SYSTEM NOTES:

Home/Auto Speaker System - Die Cast Enclosure.

*Other parts may also be available. Check with JBL for details.