



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:

LE8T-2	Cone Kit:	C8R2115
Nom. Impedance:	8 Ohm	
Dynamic Test Input V:	4	
Sweep Frequency Hz:	20-1200	
D.C. Resistance Ohms:	5.1 min/5.9 max	
Gap Gauge:	.048"	
Notes:	Bond 2 foam pads to underside of dome.	

If Not Serviceable, Replace With: LE8T-H

Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Use as last resort. Replace both units in a stereo pair.

Additional Parts Currently Available*:

Dome:	21219
Trim Gasket:	21812

HIGH FREQUENCY DRIVER:

LE20-1	Diaphragm Kit:	D8RLE20
Nom. Impedance:	8 Ohm	
Dynamic Test Input V:	6	

HIGH FREQUENCY DRIVER (Cont'd)

Sweep Frequency Hz:	1000-6000
D.C. Resistance Ohms:	3.7 min/4.2 max
Gap Gauge:	.029"
Notes:	Test With Network.
If Not Serviceable, Replace With:	035TiA
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Use as last resort. Replace both units in a stereo pair.

Additional Parts Currently Available*:

Trim Ring:	21600
------------	-------

SYSTEM SPECIFICATIONS:

Nom. Impedance:	8 ohm
Power Capacity:	35 Watts Continuous Program
Crossover Frequency:	6000 Hz
Sensitivity:	73dB (1 Watt @ 15 Feet)
Enclosure Dim:	40" x 10" x 10" D 102cm x 25cm x 25cm
Shipping Weight:	52 lbs. - 24 kg.
Additional Parts Currently Available*:	
Binding Posts:	Red: 10243 Black: 10244

*Other parts may also be available. Check with JBL for details.