



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER: 130A
 Cone Kit: C8R2220
 Nom. Impedance: 8 Ohm
 Dynamic Test Input V: 10
 Sweep Frequency Hz: 20-1200
 D.C. Resistance Ohms: 5.2 min/6.2 max
 Gap Gauge: .057"
 Notes:
 If Not Serviceable, Replace With: 2220H
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No. Slightly different.
 Replace both units in a stereo pair.

Additional Parts Currently Available*:

Dome: 21042
 Trim Gasket: 21058

HIGH FREQUENCY DRIVER: LE175
 Diaphragm Kit: D16R2410
 Nom. Impedance: 16 Ohm

HIGH FREQUENCY DRIVER (Cont'd)

Dynamic Test Input V: 3.5
 Sweep Frequency Hz: 550-1200
 D.C. Resistance Ohms: 5.9 min/7.0 max
 Gap Gauge: .031"
 Notes: 1217 Horn, 1290 Lens no longer available.

If Not Serviceable, Replace With: 2425J
 Visual Change: Yes
 Baffle Modification: No
 Exact Acoustic Replacement: No. Slightly different.
 Replace both units in a stereo pair.

SYSTEM SPECIFICATIONS:

Nom. Impedance: 8 ohm
 Power Capacity: 60 Watts Continuous Program
 Crossover Frequency: 1200 Hz
 Sensitivity: 88dB (1 Watt @ 15 Feet)
 Enclosure Dim: 29" x 20" x 16" D
 736mm x 508mm x 406mm

*Other parts may also be available. Check with JBL for details.