

## SPECIFICATIONS

DYNAMIC RANGE	90dB
BANDWIDTH, DRY DELAY	10Hz TO 20kHz 20Hz TO 17kHz
DISTORTION (THD) @ 1kHz	DRY, OdBV, 0.1% MAX. WET, OdBV, 0.5% MAX.
DELAY RANGE	DIGITAL FLANGER- 0.5 TO 5ms DIGITAL CHORUS- 2.5 TO 20ms DIGITAL DELAY- 16 TO 1024ms
MODULATION DEPTH	DIGITAL FLANGER- 0 (NONE) TO 10:1 DIGITAL CHORUS- 0 (NONE) TO 8:1 DIGITAL DELAY- 0 (NONE) TO 4:1
SWEEP SPEED	0.1SEC TO 25SEC
INPUT	510K OHM SINGLE-ENDED, 1/4" PHONE JACK, HANDLES INSTRUMENT AND SINGLE- ENDED LINE-LEVEL SIGNALS.
OUTPUT(S)	SINGLE-ENDED, 1/4" PHONE JACKS, DRIVES 600 OHMS.
MAX. OUTPUT LEVEL	+20dBm (REF. .775VRMS)
MAX. OUTPUT	+20dBm (REF. .775VRMS)
POWER CONSUPTION	5 WATTS
POWER	120 VAC, 50/60Hz
DIMENSIONS	L-10.5" X W-19" X H-1.75" (483 X 44 X 269mm)
WEIGHT	6.75lbs (14.85kg); 10lbs (22kg) SHIPPING
OPTION	220 OR 240 VAC 50/60Hz
ACCESSORY	DM-2 CONTROLLER (WITH 1/4" STEREO CORD)



<http://www.adadepot.com>