

## SPECIFICATIONS

DELAY RANGE	1 TO 1024ms
BANDWIDTH, DRY	10Hz TO 20kHz
DELAY	20Hz to 16kHz
DYNAMIC RANGE	90dB
MEMORY SIZE	256k RAM
DISTORTION (THD) @ 1KHz	dry, OdBV, 0.02% max. wet, OdBV, 0.05% max.
MODULATION DEPTH	0 (NONE) TO 4:1
SWEEP SPEED	0.1 SEC TO 10 SEC
MAX. INPUT LEVEL	+20dBm (REF..775VRMS)
MAX. OUTPUT	+20dBm (REF..775VRMS)
INPUT	SINGLE ENDED, 1/4" PHONE JACK HANDLES INSTRUMENT & LINE LEVEL SIGNALS, 500k OHM INPUT IMPEDANCE.
OUTPUTS(S)	TWO: MIX AND INVERT MIX, SINGLE ENDED, 1/4" PHONE JACKS, DRIVES 600 OHMS.
REMOTE SWITCH LOG	GROUNDING TERMINAL ENGAGES
POWER CONSUMPTION	12 WATTS
POWER	120VAC, 50/60Hz
DIMENSIONS	L-10.5" X W-19" X 1.75" (483X44X269mm)
WEIGHT	6.75lbs. (2.95kg); 10lbs (455kg) SHIPPING
OPTION	220 VAC, 50/60Hz
ACCESSORIES	DS-4 PROGRAM SELECTOR FS-2 DUAL FOOTSWITCH (INCLUDES 1/4" STEREO CORD)

