


4. SPI connector (Pin 1 SPI-D-In, Pin 2 GND, Pin 3 SPI-D-Out, Pin 4 SPI-CLK, Pin 5 +5VDC)


Toxing and the second second second




## Kit Includes:

<ul> <li>4.7MF</li> <li>0.1MF</li> <li>Red LED</li> <li>USB Connector</li> </ul>	Block <u>Connector</u> <u>Capacitor</u> <u>Capacitor</u> <u>LED</u>	1pc. 1pc. 3pc. 1pc. 1pc. 1pc. 1pc. 3pc. 4pc. 1pc. 1pc.
<ul><li>Crystal 6MZ</li><li>PCB</li></ul>		1рс. 1рс.
<ul> <li>4.7MF Capacitor</li> <li>0.1MF Capacitor</li> <li>Red LED LED</li> <li>USB Connector</li> <li>Crystal 6MZ</li> </ul>		3pc. 4pc. 1pc. 1pc.

## Schematic:





EUSB A to B Cables This cable is used to connect the EUSB port to the EUSB peripheral. A male to B male. EID-C-USB-32-930 3' EID-C-USB-32-931 6' EID-C-USB-32-932 10' EID-C-USB-32-933 15'	9.99 10.99 11.99 15.99			
Home • Back to Top Copyright © 1996-2006 Erlich Industrial Development, Corp. (EID, CORP) ALL RIGHTS RESERVED.				

www.eidusa.com